Views of Local Agencies

This project is strongly supported by the U.S. Fish and Wildlife Service as a part of its South Florida Coastal Ecosystem Program. This program is used to protect, conserve, and restore coastal living resources through the implementation of "on ground" restoration projects as well as to perform research, monitoring, and public outreach activities. The Lake Worth Lagoon Management Plan also supports this project.

DIVISION OF PLAN RESPONSIBILITIES

Cost Allocation. Section 1135(a) of the 1996 Water Resources Development Act specifies that the cost of modification to constructed Federal water resource projects for the purposes of environmental restoration is 75 percent Federal and 25 percent non-Federal. Additional guidance on Section 1135 cost sharing is provided in Engineering Pamphlet 1165-2-1 dated 15 February 1996. Table 5 details the cost sharing of the Ecosystem Restoration Report.

TABLE 5

TOTAL PROJECT COST	
** Costs include a 20% contingency	
ITEM	COST
STUDY COST	
Ecosystem Restoration Report	\$ 92,000
IN-KIND SERVICES	
Technical Plans and Specifications	\$ 45,000
Red Mangrove Plants	\$ 41,150
Permit(s)	\$ 25,000
IMPLEMENTATION COSTS	······
Non-Construction Costs	
Preconstruction, Engineering and Design *	\$ 107,600
Construction Management	\$ 52,460
Real Estate Administrative Cost	\$ 12,000
Construction Costs **	\$ 408,470
TOTAL PROJECT COST	\$ 783,680
TOTAL Federal Cost Share @ 75%	\$ 587,760
Non-Federal Cost Share @ 25%	\$ 195,920
Minus Credit for In-Kind Services	\$ 111,150
TOTAL Non-Federal Cost Share (cash contribution)	\$ 84,770

^{*} PED cost excludes \$45,000 for Technical P&S and \$25,000 for permits, which is listed as an in-kind service contribution.

Federal Responsibilities

The U.S. Army Corps of Engineers is responsible for budgeting for the Federal share of construction costs for this project. The Federal share of construction costs is estimated at \$587,760 or 75 percent of the total implementation costs. Federal funding is subject to budgetary constraints inherent in the formulation of a national Civil Works budget for a

^{**} Cost excludes \$41,150 for red mangroves, which is listed as an in-kind service contribution.

given Fiscal Year. The Corps would perform the necessary pre-construction, engineering, and design needed prior to construction. The Corps will also obtain the water quality certification, advertise, award, and construct this restoration project.

In-Kind Services

The non-Federal sponsor will provide the technical plans and specifications, red mangrove plants for restoration, and obtain the necessary permits for construction.

Non-Federal Responsibilities

The non-Federal sponsor shall provide 25 percent of the implementation costs allocated to the modification of John's Island for purposes of environmental restoration. The non-Federal share of the construction is estimated to be \$195,920 or 25 percent of the total implementation costs. The non-Federal sponsor must also assume other responsibilities before the project can be constructed. These "items of cooperation" are listed in the Recommendations section of this report. The delineation of the Federal and non-Federal responsibilities are legally defined in the PCA. The non-Federal sponsor will:

- a. Pay 100 percent of any operation, maintenance, repair, replacement, and rehabilitation cost attributable to the Environmental Restoration.
- b. Provide all additional lands, easements, and rights-of-way; borrow dredged and dredged material disposal areas; perform all relocations determined by the Federal Government to be necessary for the Environmental Restoration beyond those lands already acquired for the existing project; and provide evidence to support the Local Sponsor's legal authority to grant rights-of-entry to such lands. The necessary lands, easements, and rights-of-way determined by the Federal Government to be necessary for work to be performed under construction contract must be furnished prior to the advertisement of the construction contract.
- c. Provide or pay to the Federal Government the cost of providing all retaining dikes, wasteweirs, bulkhead, and embankments, including all monitoring features and stilling basins, that may be required at any dredged material disposal area necessary for the Environmental Restoration.
- d. Comply with applicable provisions of the Uniform Relocation Assistance and Real Property Acquisition Policies Act of 1970, Public Law 91-66, as amended by Title IV of the Surface Transportation and Uniform Relocation Assistance Act of 1987 (Public Law 100-7); the Uniform Regulations contained in 9 CFR Part 2, in acquiring lands, easement, and rights-of-way for construction and subsequent operation and maintenance of the Environmental Restoration; and inform all affected persons of applicable benefits, policies, and procedures in connection with said Act.
- e. Provide, during implementation, cash payments to meet its obligations under Article II of the Project Cooperation Agreement (PCA). Study cost and Plans and Specification costs will be funded up front by the Federal Government. Total Environmental Restoration costs will be reapportioned during the implementation period to meet the cost-sharing requirements.

SUMMARY OF COORDINATION, PUBLIC VIEWS, AND COMMENTS

The draft Environmental Assessment was distributed to the appropriate Federal, State and local agencies and is included in this report. There were no substantive comments received.

The draft Environmental Assessment contains letters and other pertinent correspondence received as a result of coordinating this project. The Ecosystem Restoration Report and EA were circulated to all governmental agencies for a 30-day review period beginning mid-November 2000.

CONCLUSIONS

This report summarizes the feasibility of modifying John's Island under the authority of Section 1135 of the Water Resources Development Act of 1986 for the purposes of providing environmental benefits in the public interest. The most practical and economical means to restore the ecosystem is based on the recommended plan in this feasibility study. The recommended plan herein provides a means of achieving ecosystem restoration by reestablishing habitat for fisheries and wildlife; removing exotic vegetation; and planting native plants for the environment. The proposed modification to John's Island is economically justified and in accordance with current Department of the Army budgetary policy.

RECOMMENDATIONS

I have given consideration to all significant aspects of the proposed ecosystem restoration of John's Island in Palm Beach County, Florida, in the overall public interest, including engineering and economic feasibility, environmental and social effects. The recommended plan described in this report provides for the optimum solution for ecosystem restoration of the study area that can be developed within the framework of the formulation concept.

I recommend that John's Island, which is a part of the Intracoastal Waterway project be modified under the general authority of Section 1135 of the Water Resources Development Act of 1986 for the purpose of ecosystem restoration. The non-Federal Sponsor shall enter into a binding agreement with the Secretary of the Army or his designated representative to perform the following items highlighted in the project cooperation agreement:

- a. Provide all lands, easements, and rights-of-way, and suitable borrow and dredged or excavated material disposal areas, and perform or ensure the performance of all relocations determined by the Federal Government to be necessary for the implementation, operation, and maintenance of the Project Modification;
- b. Provide all improvements required on lands, easements, and rights-of-way to enable the proper disposal of dredged or excavated material associated with the implementation, operation, and maintenance of the Project Modification. Such improvements may include, but are not limited to, retaining dikes, water weirs, bulkheads, embankments, monitoring features, stilling basins, and dewatering pumps and pipes;

- c. Provide, during implementation, any additional amounts as are necessary to make its total contribution equal to 25 percent of the project environmental restoration costs and 50 percent of the project recreation costs;
- d. For so long as the Project Modification remains authorized, operate, maintain, repair, replace, and rehabilitate the completed Project Modification, or functional portion of the Project Modification, at no cost to the Federal Government, in manner compatible with the Project Modification, or functional portion of the Project Modification's authorized purposes and in accordance with applicable Federal and State Laws and regulations and any specific directions prescribed by the Federal Government;
- e. Give the Federal Government a right to enter, at reasonable times and in a reasonable manner, upon property that the non-Federal sponsor, now or hereafter, owns or controls for access to the Project Modification for the purpose of inspection, and, if necessary, after failure to perform by the non-Federal sponsor for the purpose of completing, operating, maintaining, replacing, or rehabilitating the Project Modification. No completion, operation, maintenance, repair, replacement, or rehabilitation by the Federal Government shall operate to relieve the non-Federal sponsor of responsibility to meet the non-Federal Sponsor's obligations, or to preclude the Federal Government from pursuing any other remedy at law or equity to ensure faithful performance;
- f. Hold and save the United States free from all damages arising from the implementation, operation, maintenance repair, replacement, and rehabilitation of the Project Modification and any Project Modification related betterment, except for damages due to the fault or negligence of the United States or its contractors;
- g. Keep, and maintain books, records, documents, and other evidence pertaining to costs and expenses incurred pursuant to the Project Modification in accordance with the standards for financial management systems set forth in the Uniform Administrative Requirements for Grants and Cooperative Agreements to State and Local Governments at 32 Code of Federal Regulations (CFR) Section 33.20;
- h. Perform, or cause to be performed, any investigations for hazardous substances as are deemed necessary to identify the existence an extent of hazardous substances regulated under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), 42 USC 9601-9675, that may exist in, on, or under lands, easements, or rights-of-way that the Federal Government determines to be required for the implementation, operation, and maintenance of the Project Modification, except for any such lands, easements, or rights-of-way that are owned by the United States and administered by the Federal Government and except for any such lands that the Federal Government determines to be subject to the navigational servitude. The Government shall perform, or cause to be performed, al investigations on lands, easements, or rights-of-way that are owned by the United States and administered by the Federal Government. For lands that the Federal Government determines to be subject to navigation servitude, only the Federal Government shall perform such investigations unless the Federal Government provides the non-Federal sponsor with prior specific written direction, in which case the non-Federal sponsor shall perform such investigations in accordance with such written direction;

- i. Assume complete financial responsibility, as between the Federal Government and the non-Federal sponsor, for all necessary cleanup and response costs of any CERCLA regulated materials located in, on, or under lands, easements, or rights-of-way that the Federal Government determines to be required for the implementation, operation, or maintenance of the Project Modification, except for such lands, easements, or right-of-way owned by the United States and administered by the Federal Government.
- j. As between the Federal Government and the non-Federal sponsor, the non-Federal sponsor shall be considered the operator of the Project Modification for the purpose of CERCLA liability. To the maximum extent practicable, operate, maintain, repair, replace, and rehabilitate the Project Modification in a manner that will not cause liability to arise under CERCLA:
- k. Comply with the applicable provisions of the Uniform Relocation Assistance and Real Property Acquisition Policies Act of 1970, Public Law 91-646, as amended by Title IV of the Surface Transportation and Uniform Regulations contained in 49 CFR Part 24, in acquiring lands, easements, and rights-of-way, required for the implementation, operation, and maintenance of the Project Modification, including those necessary for relocation, borrow materials, and dredged or excavated material disposal, and inform all affected persons of applicable benefits, policies, and procedures in connection with said act;
- Comply with all applicable Federal and State laws and regulations, including, but nor limited to, Section 601 of the Civil Rights Act of 1964, Public Law 88-352 (42 U.S.C.2000d), and Department of Defense Directive 5500.11 issued pursuant thereto, as well as Army Regulation 600-7, entitled "Nondiscrimination on the Basis of Handicap in Programs and Activities Assisted or Conducted by the Department of the Army";
- m. Provide 25 percent of that portion of total historic preservation mitigation and data recovery costs attributable to the Project Modification that are in excess of one percent of the total amount authorized to be appropriated for the Project Modification;
- n. Under no circumstances shall the total Federal cost of the environmental restoration, including previous study costs, exceed the legislated maximum per modification total cost of 5,000,000;
- o. Not more than 80 percent of the non-Federal sponsor share of the total project cost may be credited for work-in-kind.

The recommendations contained herein reflect the information at this time and current departmental policies governing formulation of individual projects. They do not reflect program and budgeting priorities inherent in the formulation of a national Civil Works construction program nor the perspective of higher review levels within the Executive Branch. Consequently, the recommendations may be modified before they are authorized under the general provisions of Section 1135 of the Water Resources Development Act of 1986, as amended and considered for implementation funding.

JAMES G. MAY

Colonel, U. S. Army

District Engineer

Christopher P. Boruch L entenant **Col**onel, U.S. Army Acting District Engineer

REFERENCES

Dames & Moore. 1990. Lake Worth Lagoon Natural Resources Inventory and Resource Enhancement Study.

Surface Water Improvement and Management Plan (SWIM), Draft 1997. Palm Beach County Department of Environmental Resources Management.

LIST OF PREPARERS

The U.S. Army Corps of Engineers (USACOE) had the primary responsibility of preparing this document. The U.S. Fish and Wildlife Coordination Act Report was prepared by U.S. Fish and Wildlife Service, which was used in preparing the draft Ecosystem Restoration Report and Environmental Assessment. Palm Beach County Department of Environmental Resources provided input on the existing resources.

Pre	pare	ers:
<u> </u>		

Tiphanie Jinks	Plan Formulation Branch	USACOE
Paul Karch	Environmental Branch	USACOE
Paul Stevenson	Environmental Branch	USACOE

Contributors:

· David Carson	Palm Beach County Department of I	Environmental Protection
	Law Engineering and Environmental	Services
Tim Murphy	Project & Programs Division	USACOE
Paul Stevenson	Environmental Branch	USACOE
Paul Stodola	Environmental Branch	USACOE
Candida Koenig	Geotechnical Branch	USACOE
Robert Henderson	Technical Services Branch	USACOE
William Hunt	Economics Branch	USACOE
Al Fletcher	Construction Operations Division	USACOE
Lvnn Hichborn	Real Estate Division	USACOE

Reviewers:

Russ Rote	Plan Formulation Branch	USACOE
Tim Murphy	Project & Programs Division	USACOE

SECTION 1135 ECOSYSTEM RESTORATION REPORT

APPENDIX A

ENGINEERING APPENDIX

FOR

JOHN'S ISLAND PALM BEACH COUNTY, FLORIDA

U. S. ARMY CORPS OF ENGINEERS
JACKSONVILLE DISTRICT

JOHNS ISLAND – SECTION 1135 ENVIRONMENTAL RESTORATION PALM BEACH COUNTY, FLORIDA

APPENDIX A ENGINEERING

Table of Contents

Subject	Paragragh No. Pa	age No.
A. <u>INTRODUCTION</u>		
General. Restoration Plan	1 2	1 1
B. <u>HYDROLOGY AND HYDRAUI</u>	LICS	
General	3	1
C. <u>GEOTECHNICAL INVESTIGAT</u>	TIONS	
Subsurface Investigations Materials Encountered	4 5	1 2
D. CONSTRUCTION		
General Excavation and Planting Channel Revetment Disposal Area Loading Dock Construction Procedures	6 7 8 9 10 11	2 2 3 3 3 3
E. <u>RELOCATIONS</u>		
General	12	3

Table of Contents (continued)

Subject	Paragragh No.	Page No.
F. OPERATION AND MAINTENAM	<u>ICE</u>	
General	13	3
G. QUANTITIES AND COST ESTIN	MATE	
Summary of Costs	14	4
<u>LIST OF TABLES</u> (tables follow text)		
<u>Title</u>	<u>Tab</u>	ole No.
Composite Grain Size (for channel depth –4.0 NGVD) Project Cost Estimate		4-1 4-2
<u>LIST OF PLATES</u> (plates follow tables)		
<u>Title</u>	Pla	<u>ite No.</u>
Proposed Restoration Plan and Location Map Core Borings Locations Disposal Area Location	,	A-1 A-2 A-3
ATTACHMENTS (attachments follow plates)		

Core Boring Logs, Grain Size Distribution Curves, and Settling Rate Reports

JOHNS ISLAND - SECTION 1135 ENVIRONMENTAL RESTORATION APPENDIX A ENGINEERING

A. INTRODUCTION

- 1. <u>General</u>. The project is located in Lake Worth Lagoon in Palm Beach County, Florida. This Appendix presents a discussion of applicable design considerations and construction methods utilized to establish a basis for the project cost estimates. The proposed restoration plan and location map are provided on Plate A-1.
- 2. <u>Restoration Plan</u>. The proposed restoration plan would consist of removing exotic vegetation; constructing tidal channels; grading portions of the island to establish wetlands; and re-establishing native vegetation. Details of the proposed plan and the benefits that would be derived are provided in the main report and the Environmental Assessment.

B. HYDROLOGY AND HYDRAULICS

3. <u>General</u>. Palm Beach County, as project sponsor, does not plan to do any hydrodynamic modeling for Johns Island. This decision is based on the fact that the design of the restoration plan for Johns Island is very similar to the design used for restoration of nearby Munyon Island which as proven successful.

C. GEOTECHNICAL INVESTIGATIONS

4. <u>Subsurface Investigation</u>. Insitu subsurface investigations were undertaken at Johns Island for the purpose of identifying existing materials for excavation and disposal. The borings were located along the alignment of the proposed tidal channels and extend beyond the design bottom elevation of the channels (-4 NGVD)

Borings were performed using an Acker Tripod setup and a 140 pound hammer with a 30 inch drop and a split spoon sampler (1 3/8 " ID, 2" OD). Horizontal locations were measured off a baseline by tape. Elevations were estimated from the existing

survey. Accuracy is estimated at +/- 5 feet horizontal and +/- 1-foot vertical. Boring locations are provided on Plate A-2.

5. <u>Material Encountered</u>. Samples from the island show dredged spoil consisting of fine loose quartz sand with some shell and intermittent boulders or cobbles of limestone, extending to 0 to –4 NGVD. Underlying the mixed spoil is a layer of fine loose quartz sand with some silt and traces of organics. The borings in the northern half of the island did not encounter bedrock. Limestone was encountered at depth in the southern holes and was characterized as porous, hard, sandy limestone with some oyster shells. The limestone is generally below the design depth of the channels and should not interfere with excavation activities.

Laboratory testing was performed on the samples collected, including sieve analysis, moisture content, atterberg limits, organic content, and settling rate. Results are appended to the end of this section. In order to evaluate an in-water disposal alternative, a composite material was mathematically generated using samples retrieved from above the design dredging depth of —4.0 NGVD. The composite material would be classified as sand with a percent of fines at 3.9%. The composite information is shown in Table A-1. Boring logs, grain size distribution curves, and settling rate charts are included in the attachment to this appendix.

D. CONSTRUCTION

- 6. <u>General</u>. The proposed restoration plan would involve the removal of exotic vegetation, construction of two tidal channels, creation of wetland habitat, and the planting of mangroves and other native vegetation. It is anticipated that the vegetation cleared from the island would be chipped and used on site, and that the excavated material would be removed and placed in the designated disposal area. The project sponsor provided the cost for placement of the chipped vegetation (mulch) over the estimated 1.4 acres of tropical habitat. All elevations are in feet and tenths and are referenced to the National Geodetic Vertical Datum of 1929 (NGVD 29).
- 7. Excavation and Planting. The excavation of the tidal channels, creation of the proposed wetland habitat, and planting would be accomplished in accordance with the environmental restoration plan described in the main report and Environmental Assessment. The wetland habitat and areas to be planted would be graded to an approximate elevation of 1.0 feet (NGVD 29), and the channels would be constructed with a bottom width of 6 feet at an approximate elevation of -4.0 feet (NGVD 29) and side slopes of 1 vertical on 3 horizontal (1V:3H).

- 8. <u>Channel Revetment</u>. The requirement for providing bank protection to stabilize the mouths of the tidal channels was established by the project sponsor based on their experiences with similar construction on Munyon Island. They also provide the estimated quantity of rock and the cost of construction. Details of the revetment design would be included in the contract plans and specifications.
- 9. <u>Disposal Area</u>. The northern end of the designated disposal area is located approximately one mile south of the island in the submerged lands (anoxic hole) adjacent to the City of Lake Worth Municipal Golf Course. This area, which extends southward for about 1.2 miles, is designated for restoration under another project (City of Lake Worth Wetland Restoration Project Section 204) which would benefit by having additional disposal material. The location of the disposal area and general haul route is shown on Plate A-3.
- 10. Loading Dock. For cost estimating purposes, it is anticipated that a temporary loading dock, approximately 50 feet in length, would be constructed on the West Side of the island. The dock would provide access to deeper water for mooring and loading the disposal barge and off-loading the rock for construction of the tidal channel revetment. The location and design of the dock would be the responsibility of the construction contractor, subject to approval by the contracting officer.
- 11. <u>Construction Procedure</u>. After clearing and chipping operations are sufficiently complete, excavation of the tidal channels could commence. Construction of the channels should begin at the upland terminus and proceed to the island's edge to minimize tidal intrusion. Portions of the wetland habitat creation and planting could be accomplished concurrently.

E. RELOCATIONS

12. <u>General</u>. The project sponsor would be responsible for providing all the lands easements, rights-of-way, relocations, and disposal (LERRD) as required for construction of the proposed project features.

F. OPERATION AND MAINTENANCE

13. <u>General</u>. The contractor would be responsible for all maintenance during the construction contract. After completion of the construction contract, the project sponsor would assume the responsibility for operating and maintaining the project.

A discussion of the maintenance and monitoring requirements is presented in the Environmental Assessment and the main report.

G. QUANTITIES AND COST ESTIMATE

14. <u>Summary of Costs</u>. The estimates of first cost for construction of the recommended plan were prepared using M-CACES software and are presented in Table A-2. The estimate includes a narrative and summary cost showing quantity, unit cost, and the amount for contingencies for each cost item.

The costs have been prepared for an effective date of November 2000.

					TABLE A-1	A-1		•		
			JOHNS IS	SLAND EN	JOHNS ISLAND ENVIRONMENTAL RESTORATION	TAL REST	DRATION			
			COMPOSI	TE GRAIN (COMPOSITE GRAIN SIZE (for channel depth -4.0 NGVD)	annel depth	4.0 NGVD			
CB	SAMPLE	%				% FINER	% FINER BY SIEVE NUMBER	UMBER		
	NO.	FINES		4	10	20	40	09	100	200
CB-1	2	1.7		37.4	33.0	26.6	12.6	6.6	3.7	1.7
CB-2	ည	2.0		99.5	98.2	96.1	84.4	46.1	11.4	2.0
CB-3	2	6.0		97.6	94.7	6.06	71.0	25.3	4.3	0.0
	2	3.2		6.66	99.7	98.0	66.2	19.1	5.6	3.2
CB-4	2	2.5		91.2	85.8	74.5	40.2	13.5	4.5	2.5
	4	5.7		100.0	93.6	98.0	66.7	19.6	8.1	5.7
CB-5	-	4.1		97.7	95.7	20.7	70.8	40.5	14.2	4.1
	ည	4.6		100.0	8.66	98.0	64.2	17.4	6.7	4.6
CB-6	-	6.0		8.66	98.9	94.0	35.7	5.7	2.0	6.0
	4	5.4		83.1	77.9	67.1	39.0	16.1	8.4	5.4
CB-7	2	11.5		97.7	97.0	95.1	75.2	36.4	17.0	11.5
MEAN		3.9		91.3	89.1	84.5	6.95	22.4	7.8	3.9

Fri 03 Nov 2000 Eff. Date 12/01/00 U.S. Army Corps of Engineers

PROJECT JIF001: John's Island - Ecosystem Restoration Report

John's Island Restoration

Section .

TIME 11:16:21

TITLE PAGE

John's Island Ecosystem Restoration Report Palm Beach County, Florida

TABLE A-2

Designed By: Jacksonville District

Estimated By: M Fascher

Prepared By: Kirby Ray Clifton

Preparation Date: 11/02/00

Effective Date of Pricing: 12/01/00 12779-2 ion.

Sales Tax: 6.00%

This report is not copyrighted, but the information contained herein is For Official Use Only.

MCACES GOLD EDITION Composer GOLD Software Copyright (c) 1985-1994 by Building Systems Design, Inc. Release 5.30A

LABOR ID: DADE98 EQUIP ID: REG399 Currency in DOLLARS

CREW ID: NAT99A TABLE A-2 PROJECT JIF001: John's Island - Ecosystem Restoration Report

John's Island Restoration

TITLE PAGE

TIME 11:16:21

The original cost estimate has been updated to include the construction and dismanteling of a temporary dock on the west side of the island. The dock is necessary for the loading of spoil onto barges and for the unloading of the stone.

plan is to ecolocically restore a 6.5-acre spoil island by removing and chipping approximately 5 acres of exotic plants, constructing tidal channel system by removing 17,000 cy of material and planting approximately 13,800 red mangroves, 11,400 plugs of cordgrass, and 500 tropical hammock plants. Assume that excavated material will be disposed of offsite approximately 2 miles away with no disposal fees or disposal area costs.

Contingencies of 20% were used based on the level of design.

E&D costs were provided by design engineer and project manager. S&I costs are based on using percentages as directed by the project manager(9%).

U.S. Army Corps of Engineers

TIME 11:16:21

SUMMARY PAGE 2

PROJECT JIF001: John's Island - Ecosystem Restoration Report

John's Island Restoration

** PROJECT OWNER SUMMARY - Sub Ele (Rounded to 10's) **

OUANTY UOM CONTRACT CONTINGN ESCALATN TOTAL COST UNIT 01 Johns Island Restoration A Construction Cost 0.1 A-06 Fish and Wildlife Facilities 01. A-06-03 Wildlife Facilities & Sanctuary 01. A-06-03_73 Habitat and Feeding Facilities 01. 61,670 12,330 0 74,010 A-06-03_73_01 Mob and Demob 01. 10,530 2105.33 8,770 1,750 A-06-03 73_02 Complete Clearing 5.00 ACR O 01. A-06-03_73_03 Limestone Boulders 500.00 TNS 21,680 4,340 26,010 52.02 01. 7,390 1,480 5.00 ACR 0 8,870 1773.74 01. A-06-03_73_05 Chipping A-06-03_73_06 Excavation/Fill 17000 CY 113,160 22,630 0 135,790 01. 48,060 40,050 8,010 0 A-06-03_73_08 Temporary Loading Dock 01. 500.00 EA 69,040 13,810 0 82,850 165.70 A-06-03_73_09 Tropical Hammocks 01. 11400 EA 18,630 3,730 1.96 A-06-03 73 10 Cordgrass ٥ 22,350 01. A-06-03_73_11 Red Mangrove 13800 EA 34,300 6,860 41,150 01. ------374,680 74,940 TOTAL Habitat and Feeding Facilities _____ TOTAL Wildlife Facilities & Sanctuary 374,680 -----TOTAL Fish and Wildlife Facilities 374,680 74,940 0 _______ 374,680 74,940 0 449,620 TOTAL Construction Cost 01. B Non-Construction Cost B-01 Lands and Damages 01. 0 B-01-01 Lands and Damages 10.000 2.000 12,000 01. ______ 10.000 2,000 0 12.000 TOTAL Lands and Damages B-30 Preconstruction, Engr & Design 01. B-30- 2 Plans and Specifications 148,000 29,600 0 177,600 01. TOTAL Preconstruction, Engr & Design 148,000 29,600 177,600 01. B-31 Construction Management (S&I) 43,720 8,740 0 01. B-31-01 Construction Management (S&I) 52.460

U.S. Army Corps of Engineers

PROJECT JIF001: John's Island - Ecosystem Restoration Report

John's Island Restoration

** PROJECT OWNER SUMMARY - Sub Ele (Rounded to 10's) **

SUMMARY PAGE 3

TIME 11:16:21

1		QUANTY UOM	CONTRACT	CONTINGN	ESCALATN	TOTAL COST	UNIT
	TOTAL Construction Management (S&I)		43,720	8,740	0	52,460	
	TOTAL Non-Construction Cost	•	201,720	40,340	0	242,060	
	TOTAL Johns Ísland Restoration	.	576,400	115,280	0	691,680	
	TOTAL John's Island	•	576,400	115,280	0	691,680	

Fri 03 Nov 2000 Eff. Date 12/01/00 ERROR REPORT

U.S. Army Corps of Engineers

PROJECT JIF001: John's Island - Ecosystem Restoration Report

John's Island Restoration

TIME 11:16:21

ERROR PAGE

No errors detected...

* * * END OF ERROR REPORT * * *

LABOR ID: DADE98 EQUIP ID: REG399 Currency in DOLLARS

CREW ID: NAT99A UPB ID: NAT95A

Fri 03 Nov 2000 Eff. Date 12/01/00 TABLE OF CONTENTS U.S. Army Corps of Engineers

PROJECT JIF001: John's Island - Ecosystem Restoration Report

John's Island Restoration

CONTENTS PAGE

TIME 11:16:21

SUMMARY REPORTS SUMMARY PAGE

No Detailed Estimate...

No Backup Reports...

* * * END TABLE OF CONTENTS

Fri 03 Nov 2000 Eff. Date 12/01/00

TOTAL John's Island

U.S. Army Corps of Engineers

PROJECT JIF001: John's Island - Ecosystem Restoration Report

576,400 115,280

John's Island Restoration

SUMMARY PAGE 1

0 691,680

TIME 11:16:21

** PROJECT OWNER SUMMARY - Culvert (Rounded to 10's) **

QUANTY UOM CONTRACT CONTINGN ESCALATN TOTAL COST UNIT

CREW ID: NAT99A UPB ID: NAT95A

ATTACHMENT

Core Boring Logs, Grain Size Distribution Curves, and Settling Rate Reports

DRTI	LING	LO	G DIVISION		ALLATI			HEET I
. PROJE			South Atlantic		IZE AND		of BIT See Remarks	0F 1
West	Palm B		- Johns Island				VATION SHOWN (TBM or MSL)	
			etes or Station)	N	GVD-2	9 Hori	zontal Datum: FLE NAD-83	
	9,156 '		2,404				S DESIGNATION OF DRILL	
Corp	s Of En	ginee			CKET T		VERBURDEN SAMPLES TAKEN	
	NO. (As :		on drawing title		sturbe		undisturbed: 0	
	OF DRIL	•	CB-JI00-1	14. T	OTAL N	UMBER	OF CORE BOXES 1 (Box 1)	
	Gregory						UND WATER +0.3	
. DIREC	TION OF	HOLE		16. 0	ATE HO		TARTED COMPLETED	
⊠ VE	ERTICAL		INCLINED				4 Jul 00 24 Jul 00	
. THICK	NESS OF	BURG	DEN Ft.				OF HOLE +3.8 Ft.	
. DEPTH	DRILLE	D INT	0 ROCK 0.0 Ft.	18. 1	DIAL CO	RE OFG	COVERY FOR BORING 54 %	
. TOTAL	DEPTH	OF HO	LE 10.5 Ft.		Papie			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATER (Description)	RIALS	CORE REC	SAMPLE	REMARKS Bit or Barrel	BLOWS/ .5'
		-		······	+	W.E	3.8	
3.8	.0	1000	SAND, fine quartz, loose, dam	10		\vdash	J.6	1
			tan, trace fine shells, trace	ιρ,	53	١, ا	SPLIT SPOON	2
		 	sandy limestone gravel, fine.	top	"	'		4
]:::::	2" organic, many lenses of limestone. SP		-	\vdash	2.3	6
	:				67	2	SPLIT SPOON	
		[::::			67	D-2	•	24
	-				<u> </u>	<u> </u>	.8	
	:	/::::	(Fill Material)		1		ADI 17	12
	-		• • •		80	3	SPLIT SPOON	14
		[[][]			-	 	7	17
Ì	-							4
					33	4	SPLIT SPOON	9
-2.2	6.0						-2.2	5 -
-2.7	6.5	$\mu \mu$	from 6.0' to 6.5' very peaty			_	_	1
	-		L SAND, fine quartz, loose,		80	5 D-5	SPLIT SPOON	1
			saturated, dark brown, some organics, trace silt. SP				-3.7	3 -
	-	[::::]	Signification of the second					2 -
	-				0	0	SPLIT SPOON	3
-5.2	9.0						-5.2	5
	<u> </u>	ш	Silty SAND, fine quartz, loose	•				3 -
	:		saturated, brown, trace silt,	•	67	6 D-6	SPLIT SPOON	3
-6.7	10.5		trace clay. SM		1	ا ۳۰۰	-6. <i>T</i>	3 -
			Soils are field visually classifi in accordance with the Unifie Classification System.				140# HAMMER WITH 30" DROP USED ON 2" SPLIT SPOON (I 3/8" ID X 2" OD) HORIZ POSITION EST BY TAPE ACCURACY +/- 5 FEET	
						-		
	-	1 1						E
								F
	-							
	-							1 1 1 1
								1 1 1 1
								1 1 1 1
								1 1 1 1
			IS EDITIONS ARE OBSOLETE. PI					1 1 1 1

DRII	LING	LO	6 DIVISION			CKEOD			ET I OF I
. PROJE	CT							of BIT See Remarks	<u>, , , , , , , , , , , , , , , , , , , </u>
			- Johns Island etes or Station)		II. DA	TUM FO	RELEV	VATION SHOWN (TBM of MSL)	
X=96	18,331	/=84						zontal Datum: FLE NAD-83 'S DESIGNATION OF DRILL	
3. DRILL	ING AGE	NCY			Ac	ker Ti	i-pod	f ⁱ	
	s Of Eng		on drawing title			TAL NO		VERBURDEN SAMPLES TAKEN undisturbed: 0	
and fil	e number)	CB-JI00-2					OF CORE BOXES (Box 1)	
	of ORILI Gregory	LER						UND WATER Not Observed	\neg
	TION OF	HOLE					E S	TARTED COMPLETED	
⊠ve	RTICAL		INCLINED		<u> </u>			5 Jul 00 25 Jul 00	
. THICK	NESS OF	BURG	DEN Ft.					OF HOLE 4.5 Ft.	
. DEPTH	ORILLE	D INT	O ROCK 0.0 Ft.		18. TO	TAL CO	RE OF G	COVERY FOR BORING 77 %	
. TOTAL	DEPTH	OF HO	DLE 10.5 Ft.			Papie	nik		
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATE (Description)	ERIAI	LS	CORE REC	SAMPLE	REMARKS Bit or Barrel	.5°
4.5	.0	-				1		4.5	
	•		SAND, fine quartz, loose, mo	oist,					1
			tan, upper 3" organic, trace shells, trace medium sand.	e fine SP	?	87	1	SPLIT SPOON	1
			Silvano, inducation control			L	L	3,0	1
			(Fill Material)				2		2
			(i in riscoriui)			67	D-2	SPLIT SPOON	3
	-					<u> </u>	 	1.5	5
		 }}				53	3	SPLIT SPOON	2 3
	-					53			6
]		saturated, light gray			 	\vdash	.0	2
	_					67	4	SPLIT SPOON	4
	-							-1.5	3
	_							,,,	7
	-					100	5 D-5	SPLIT SPOON	2
	-					L	0 0	-3.0	2
									1
-4.0	8.5					67	6	SPLIT SPOON	1
	-		SAND-Silty SAND, fine quar loose, dark brown, trace silt			L		<i>−4.5</i>	1
	. 1		trace organics. SP-SM	ι,			7		2
	_					100	D-7	SPLIT SPOON	3 -
-6.0	10.5	<i>1</i> 41	Soils are field visually class	ified ied S	oils			-6.0 140# HAMMER WITH 30" DROP USED ON 2" SPLIT SPOON	
	-		Classification System.					(1 3/8" ID X 2" OD)	Ė
,	1							HORIZ POSITION EST BY TAPE ACCURACY +/- 5 FEET	E
	1								Ē
	4								F
	-								E
	3								E
İ									E
Ì									ŧ
	=								ŧ
	7								F
l	=								F
	_								E
1	7								F
	‡								F
	7								F
	7								F
1]			F
IG FORM	1836 P	REVIO	US EDITIONS ARE OBSOLETE.	PROJE	ECT	ļ		HOLF NIME	R
NG FORM	1 1836 PF	REVIO	US EDITIONS ARE OBSOLETE.	PROJE West		Beac	h - J	phns Island CB-JI00-	

001111	VIC I O	C DIVISION	INSTA				HEET 1
DRILLI	NO LO	South Atlantic		kson		strict of BIT See Remarks	0F 1
	n Beach	- Johns Island				ATION SHOWN (TBM or MSL)	
		ates or Station)				zontal Datum: FLE NAD-83	
X=969,19 DRILLING A		2,110		NUFAC ker Tr		S DESIGNATION OF DRILL	
Corps Of	Enginee		13. TO	TAL NO), OF 0	verburden samples taken	
. HOLE NO. (and file nu	(As shown mber)	on drawing title CB-JI00-3		turbe		undisturbed: 0	
. NAME OF D		05 4100 0				OF CORE BOXES 1 (Box 1)	
L.C. Greg			16. ELE	VATIO	ON GRO	UND WATER 2.5 TARTED COMPLETED	
DIRECTION VERTION			10. 02	16 1106		6 Jul 00 26 Jul 00	
			17. ELE	VATIO	N TOP	OF HOLE 5.0 Ft.	
. THICKNES		OROCK 0.0 Ft.				COVERY FOR BORING 86 %	
		DLE 10.5 Ft.		NATUF Papier		EOLOGIST	Ī
ELEV. DEP	H	CLASSIFICATION OF MATERIA (Description)	LS	CORE REC	SAMPL	REMARKS Bit or Barrel	BLOWS/
5.0	0					5.0	
	-700	SAND, fine quartz, loose, damp,					1
ł	7/0	tan, occasional limestone boulders and cobbles, trace		67		SPLIT SPOON	2
	-]	organic, trace fine shells. SP				3.5	2
]	_					3
	3			80	D-2	SPLIT SPOON	4 -
] ///	(Fill Material)		<u> </u>		2.0	7
	- }///	(i iii material)		١٠			4
}	4			100	3	SPLIT SPOON	4 -
	#//			ļ		.5	4
_ 2 _ 5	<u>, </u>				.	ON IT ORGALI	
<u>-:3 5:</u>	3 1	from 5,3' to 5.5' peat layer		73	4	SPLIT SPOON	<u> </u>
	SAND-Silty SAND, fine quartz,			\vdash	-1.0	- 1 E	
	4/11	loose, saturated, brown, trace		,,,,	5	SPLIT SPOON	- 2 - 4
	fine shells, trace silt, trace organics. SP-SM		100	D-5		-	
	4/11					<i>-2.5</i>	
	# ///			80	6	SPLIT SPOON	<u></u>
	- 1 /1/1			1 80	°		-
	7/1			ļ		-4.0	- <u>'</u>
	<u> </u>	1		100	7	SPLIT SPOON	5
٠. ا	▗᠆Ϳʹ╢			```	D-7 -	-5.5	7
- <i>5.5</i> 10.	للناح						<u> </u>
	4	Soils are field visually classified	7 ± !! =			140# HAMMER WITH 30" DROP USED ON 2" SPLIT SPOON	F
	‡	in accordance with the Unified S Classification System.	OHS			(1 3/8" ID X 2" OD)	F
	1	Signation dystem.					
	コ					HORIZ POSITION EST BY TAP ACCURACY +/- 5 FEET	~ F
	‡					,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	F
	4						F
	1						F
	1				}		E,
	7						F'
	1						E
	4						F
	7						E
		1		İ			E
	7	İ					E
	3			l			E
	7						F
1	}	·		1			E
	_{-}			1			E,
	7						E'
1	7						E
1	1			1			F
	7						Г
	4			Ι΄.			t
	La and						F.
		US EDITIONS ARE OBSOLETE. PROJ					

			Jan Wassian	HUST	LLATI	ON.	HOIE NO.CB-310			
DRIL	LING	LOC	South Atlantic		ckson'			HEET I		
PROJEC				10. SI	ZE AND	TYPE	OF BIT See Remarks	i-		
			- Johns Island	II. DATUM FOR ELEVATION SHOWN (TBM or MSL) NGVD-29 Horizontal Datum: FLE NAD-83						
	10N <i>(Coo</i> : 9.165 Y=		tes or Station) 725							
. ORILLI	NG AGENO	CY .		12. MANUFACTURER'S DESIGNATION OF DRILL Acker Tri-pod						
	Of Engi			13. 10	TAL NO	, of 0	VERBURDEN SAMPLES TAKEN			
	NO. (As shi e number)	OWN C	n drawing title CB-JI00-4		turbe		undisturbed: 0			
	OF DRILLE	R	00 0100 7				OF CORE BOXES 1 (Box 1)			
L.C. G	regory						UND WATER 1.3 TARTED COMPLETED			
	TION OF H			16. UA	HOL		7 Jul 00 27 Jul 00			
⊠ VE	RTICAL	LJ IN	ICLINED	17. FL	EVATIO		OF HOLE 3.3 Ft.			
	NESS OF E						COVERY FOR BORING 71 %			
			ROCK 0.0 Ft.				EOLOGIST			
. TOTAL			E 8.7 Ft.	C.	Papier					
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIA (Description)	LS	CORE REC	SAMPLE	REMARKS Bit or Barrel	BLOWS/		
3.3	.0						3.3			
 		77	SAND, fine quartz, loose, moist,		1			2		
1	#		tan, trace fine shells, occasiona	i	73	1	SPLIT SPOON	1		
- 1	4		limestone cobbles and boulders. SP		1		1.8	3		
	- 4/							4		
- 1	4/		(Fill Material)		67	2	SPLIT SPOON	4		
1	-					D-2	.3	6		
	#				!	$\vdash \dashv$		3		
- 1	<u> </u>		from 3.5' becoming light gray		67	3	SPLIT SPOON	4		
	₫:							5		
-1.3	4.6	44	CAMP CITY CAMP				-1.2	Ť		
	-7:	:	SAND-Silty SAND, organic, fine quartz, loose, saturated, dark		67	4	SPLIT SPOON	o		
	7.	1	brown, trace silt, little organics.		0'	4	· · · · · · · · · · · · · · · ·	-		
1	1	11	SP-SM		<u> </u>		-2.7			
	- 1	11				_	-	7		
-3.8	7.1		more silt with depth		87	5	SPLIT SPOON	2		
	4	刊	LIMESTONE, hard, porous, sandy	1,	<u> </u>		-4.2	20		
	4:	井	oyster bed.		68	6	SPLIT SPOON	37		
-5.4	8.7	#			08	D-6	-5.4 SPLIT SPOUN	50 48		
-3.4	• • • •				1		XXX.			
1	}		Soils are field visually classified				140# HAMMER WITH 30" DROP	Ŀ		
Ì	_}		in accordance with the Unified S Classification System.	ols			USED ON 2" SPLIT SPOON (I 3/8" ID X 2" OD)	t		
	\exists		Gassingation System.				•	E		
ł	7						HORIZ POSITION EST BY TAPE	: E		
l	4						ACCURACY +/- 5 FEET	F		
[1							F		
	1	- [•		
	듹	-						ļ		
	Ŀ							<u> </u>		
	3	-				[t		
	Ŧ							E		
l	7							F		
	4	- 1						F		
	‡							- 1		
1	1							ļ.		
1	\exists							Ŀ		
		- 1						t		
]							E		
]									
	4							F		
	سالست							-		
	بما يينا									
	ببانيييات									
	ببليسيين									
	بينايينيين التنيين									
	ushmannanhaman									
	بيليييين باليينانينا		S EDITIONS ARE OBSOLETE. PROJ							

DIVISION		INSTA	LLATI	ON	HUIE NU	.CB-0100 SH	EET T	
DRILLING LOG South Atlantic	>	Jac	ckson	ville D			OF I	
PROJECT					OF BIT See Remarks			
West Palm Beach - Johns Island LOCATION (Coordinates or Station)					ATION SHOWN (TBM of	•		
X=969,175 Y=841,535					zontal Datum: FLE NA S DESIGNATION OF DR			
DRILLING AGENCY		Aci	ker Tr	i-pod			ſ	
Corps Of Engineers HOLE NO. (As shown on drawing title		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN						
and file number) CB-JI	00-5		turbe		undisturbed: 0			
NAME OF DRILLER					OF CORE BOXES 1 (Bo	X 2)		
L.C. Gregory					UND WATER 1.8 FARTED COMPLETED		I·	
DIRECTION OF HOLE		IB. UA	IE MUL		7 Jul 00 27 Jul 00		- 1	
☑ VERTICAL ☐ INCLINED		17 FLE	VATIO		OF HOLE 3.8 Ft.			
THICKNESS OF BURDEN Ft.	,				COVERY FOR BORING	7 %		
DEPTH DRILLED INTO ROCK 0.0 Ft.					EOLOGIST			
TOTAL DEPTH OF HOLE 9.7 Ft.			Papier					
	ON OF MATERIAL cription)	.S	CORE REC %	SAMPLE	REMARKS Bit or Bar		BLOWS/	
3.8 .0					3.8			
-//// SAND, fine quart						_	1	
tan, trace shells limestone cobble	, occasional s and boulders.		80	D-1	SPLIT	SPOON _	3	
SP			L		2.3		5 -	
- I → I → I						_	8 -	
1 4///			67	2	SPLIT	SPOON	9 -	
					.8	_	12 -	
(Fill Material)							10	
1 4 88	a.		27	3	SPLIT	SPOON _	9	
4///					7	-	9 -	
-1.2 5.0							3	
SAND-Silty SAN	D. fine quartz.		47	4	SPLIT	SPOON -	1	
loose, saturated	, dark brown,				-2.2	-	1	
trace silt, trace	organics. SP-St	М			۷.۵		<u> </u>	
3/4.11			60	5_	SPLIT	SPOON -	2	
			"	D-5		_	2 -	
1 -4/11					-3.7			
more silty with c	ay @ 8.0'						<u></u>	
-4.6 8.4 - 1.1.1			67	6	SPLIT	SPOON _	3	
LIMESTONE, har	u, porous, gray.				-5.2		-6	
-5.9 9.7			100	7	-5.9 SPLIT	SPOON -	30 50	
-5.9 5.1							<u> </u>	
Soils are field vi					Boring advanced v			
in accordance w		oils			140# HAMMER WIT USED ON 2" SPLIT		E	
Classification Sy	3161111				(1 3/8" ID X 2" OI))	F	
]					•		F	
1					HORIZ POSITION I		F.	
-					AUCUNAUT T/T D		F ¹	
1 1 1							ţ	
							Ł	
]							F	
		,					F	
				l			<u> </u>	
							ŧ	
				ľ			ţ	
-							F	
-				l			E	
							F.	
7							- 1	
4							ţ	
1 4 1			1 1				Ł	
1			1				ŀ	
							L.	
							E	
							-2	
							‡ = = =	
G FORM 1836 PREVIOUS EDITIONS ARE OBSOLE								


DRIL	LING	LO	G DIVISION South Atlantic	1	ckson		SHEE strict C	T 1
PROJEC	Ť		Court Monte	10. SI	ZE AND	TYPE	OF BIT See Remarks	
West	Palm Be	ach	- Johns Island otes or Station)				ATION SHOWN (TBM or MSL)	
X=969	9,264	Y=84					zontal Datum: FLE NAD-83 S DESIGNATION OF DRILL	\dashv
ORILLI	NG AGEN			Ac	ker Tr	i-pod		
			on drawing title		Sturber		VERBURDEN SAMPLES TAKEN undisturbed: 0	
	e number,		CB-JI00-6	***			OF CORE BOXES 1 (Box 1)	\neg
NAME (of DRILL regory					_	UND WATER 1.5	
. DIREC			***************************************	16, 07	TE HOL		ARTED COMPLETED	
⊠ VE	RTICAL		NCLINED				5 Jul 00 25 Jul 00 OF HOLE 4.0 Ft.	-
. THICK	NESS OF	BURG	DEN Ft.				COVERY FOR BORING 69 %	
. DEPTH	DRILLE	TNI C	DROCK 0.0 Ft.	19. SI	GNATU	E OF G	EOLOGIST	\dashv
. TOTAL	DEPTH		LE 10.5 Ft.	<u> </u>	Papier			_
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATER (Description)	IALS	CORE REC	SAMPLE	REMARKS Bit or Barrel	.5;
4.0	.0						4.0	
	•		SAND, fine quartz, loose, dam	p,		١, ا		<u>'</u>
			tan, trace fine shells, trace organics, occasional limestoni	e	67	D-1		<u>! </u>
	-		cobbles and boulders. SP		·	_	2.0	<u>!</u>
	-				1,,	,		<u> </u> - -
					47	2	-	4
- 1	1						7.0	7
					47	3		7
			saturated, light gray, occasion limestone gravel	nal	"			В
	-		initestorie gravei					6 -
	-				47	D-4	SPLIT SPOON	3 -
	-						-2.0	3 -
			(Fill Material)					3
			(Fill Material)		100	5		3
-3.3	7.3		SAND-Silty SAND, fine quartz	,			0.0	2 <u> </u>
	-		loose, saturated, dark brown,		1	6		<u> </u>
	=		little organics, trace silt. SP-	-SM	73	D-6		3
	-				ļ			3 F
					100	7	**************************************	3
-6.0 -6.5	10.0		Silty SAND, loose, saturated,		"	8	 -	5 -
-0.5	10.5	41.1.	dark brown, trace clay, little					丰
	-		organics. SM				140# HAMMER WITH 30" DROP USED ON 2" SPLIT SPOON	F
İ	-		Soils are field visually classifi	ed			(1 3/8" ID X 2" OD)	E
			in accordance with the Unifie Classification System.	d Soils			HORIZ POSITION EST BY TAPE	F
	-		Glassification System.				ACCURACY +/- 5 FEET	ŧ
	-							ŧ
j	-							F
İ	=							E
	_							F
	3				1			E
					1			Ŀ.
	-							ŧ
	=							ŧ
	_				1			F
	-							E
	_							E
	=							E
- 1	-							E
								E
	-							ŧ
								F
l	=				1			þ
		1			1			ļ.
1		1 '						
			US EDITIONS ARE OBSOLETE.	ROJECT			HOLE NUMBE	

			- IDIVISION	TINCT	ALLATI	ON	HOIE NO.CB-JI	
DRIL	LING.	LO	6 South Atlantic		ckson			SHEET 1 OF 1
PROJE							OF BIT See Remarks	
			- Johns Island				VATION SHOWN (TBM or MSL)	
			ates or Station)	NO.	SVD-2	9 Hori	zontal Datum: FLE NAD-83	
	9,250		11,775				'S DESIGNATION OF DRILL	
	ING AGE				ker Ti			
			on drawing title		OTAL NO sturbe		VERBURDEN SAMPLES TAKEN	
	e number		CB-JI00-7				undisturbed: 0	
. NAME	OF DRILL	.ER					OF CORE BOXES 1 (Box 2)	
L.C. 0	Gregory						OUND WATER 1.5	
. DIREC	TION OF	HOLE		16. DA	TE HO		TARTED COMPLETED	
⊠v£	ERTICAL		INCLINED	ļ			7 Jul 00 27 Jul 00	
THICK	NESS OF	BUR	DEN Ft.				OF HOLE 2.0 Ft.	
							COVERY FOR BORING 72 %	
			O ROCK 0.0 Ft.				BEOLOGIST	
. TOTAL	. DEPTH	OF HO	DLE 10.5 Ft.	U.	Papie		r	
LEV.	DEPTH	LEGENO	CLASSIFICATION OF MATERI (Description)	ALS	CORE REC	SAMPLE	REMARKS Bit or Barrel	BLOWS/
		-			┼	·	 	
2.0	.0						2.0	
	1	:::::::	SAND, fine quartz, loose saturated, dark brown, some		1	١.		Woh
į	-	::::::	organics, little fine shells,		33	1	SPLIT SPOON	
	-		limestone gravel, occasional		1		.5	1
	1		cobbles. SP					1
1	-				80		SPLIT SPOON	4
	_				"	3		
	-		(Fill Material)		<u></u>	ļ	-1.0	6
	-	,	(i iii riotoridi)					3
	4				87	0-4	SPLIT SPOON	2
					1	"-"	-2.5	4
ايا		;;;;; <u> </u>			—	5	2.0	1
-3.0	5.0_				┨ 。	-	20177 60001	
1			SAND-Silty SAND, fine quartz,		67	6	SPLIT SPOON	
į	-		loose, saturated, brown, trace silt, trace organics. SP-SM			١	-4.0	3
1			siit, trace organics. 3r-3M					5 -
					67	7	SPLIT SPOON	6
	7				1 6,	D-7		
					<u></u>		<i>-5.5</i>	6
	-				i	i		1 -
- 1	7		•		80	8	SPLIT SPOON	2
1					1		-7.0	3
	·				-	9	-7.0	7
-7.5	9.5	إبان			١	-	COLUT CROOM	
- 1		'T'	LIMESTONE, hard, gray, oyster	•	93	ю	SPLIT SPOON	22
-8.5	10.5	$I_{T}I$	bed.				<i>-8.5</i>	10
			Soils are field visually classifier in accordance with the Unified Classification System.	d Soils			140# HAMMER WITH 30" DROP USED ON 2" SPLIT SPOON (1 3/8" ID X 2" OD)	
			classification System.				HORIZ POSITION EST BY TAP	e E
ŀ	-						ACCURACY +/- 5 FEET	Ł
l	7							F
l	4							F
l	4				1			Ł
ł	7							F
İ	ᆿ							_
	7							Ŀ
- 1	7							F
i		1						Ŀ
ł	7	l						ŀ
į	- 1							F
- 1	ㅋ							F
I	7	1						F
I	ゴ	l						- F
	-1							Ŀ
İ	1							F
1	t							Ŀ
	긕	1						F
	1	1						t
1	4							ŀ
ļ	ュ							Ļ
ı	4				1			i.
	7	,						F
1					1			Ŀ
	극	į	·					
FORM	1830 PF	EVIO		JECT			hole Nu ohns Island CB-JI(MBER

SUMMARY OF LABOK... ORY TEST RESULTS

Johns Island Environmental Restoration Project U. S. Army Corps of Engineers LAW Project No. 50160-8-0025

		_									-,			-				- -	
Organic	Content (%)	727	5.7	ö						0.0									90
Plasticity Index	(%)	,		QN	2			QN			QN	JN:	QN			QN			
Plastic Limit	(%)			dN				dN			QV		αN			QN			
Liquid Limit	(%)			αN				ď			QN		ďN			αN			
Percent	Fines (%)	1.7			2.0	3.7	60	3.2		2.5	5.7	4.1	4.6	0.9	5.4	3.3	11.5		2.4
Moisture	Content (%)		225.5	32.3	24.8			31.0	0.4						20.0			24.9	
		GP			SP	SP	SP	SP		SP	SP-SM	SP	SP	SP	SP-SC	SP	SP-SM		SP
Depth	(Feet)	1.5 - 2.5	6.0 - 7.2	9.0 - 10.0	6.0 - 7.5	9.0 - 10.5	1.5 - 2.7	6.0 - 7.5	9.0 - 10.5	1.5 - 2.5	4.5 - 5.5	0.0 - 1.2	6.9 - 0.9	0.0 - 1.0	4.5 - 5.2	7.5 - 8.6	1.5 - 2.0	3.0 - 4.3	6.0 - 7.0
Sample	No.	2	5	9	5	7	2	2	7	2	4	1	2	1	4	9	2	4	7
	Boring No.	CBJI00-1	CBJ100-1	CBJ100-1	CBJ100-2	CBJ100-2	CBJ100-3	CBJ100-3	CBJ100-3	CBJ100-4	CBJ100-4	CBJ100-5	CBJ100-5	CBJ100-6	CBJ100-6	CBJ100-6	CBJ100-7	CBJ100-7	CBJ100-7
	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plasticity Index	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plasticity Index No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%)	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plasticity Index No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) C 2 1.5-2.5 GP	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plasticity Index No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) 2 1.5 - 2.5 GP 1.7 (%) (%) 5 6.0 - 7.2 225.5 (%) (%)	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plastic Limit Plasticity Index No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 2 1.5 - 2.5 GP 1.7 (%) (%) (%) 5 6.0 - 7.2 225.5 32.3 NP NP NP	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plastic Limit Plasticity Index No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 1.5 - 2.5 GP 1.7 (%) (%) (%) 5 6.0 - 7.2 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP 5 6.0 - 7.5 SP 24.8 2.0	Sample Depth Unified Soil Moisture Percent No. Liquid Limit Flastic Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 2 1.5 - 2.5 GP 1.7 (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 NP NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP 7 9.0 - 10.5 SP 3.7 NP NP NP 2 1.5 - 2.7 SP 0.9 0.9 NP NP NP	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 2 1.5 - 2.5 GP 1.7 (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 NP NP NP 6 9.0 - 10.0 SP 24.8 2.0 NP NP 7 9.0 - 10.5 SP 3.7 NP NP 2 1.5 - 2.7 SP 0.9 NP NP 5 6.0 - 7.5 SP 31.0 32 NP NP	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP 2 1.5 - 2.7 SP 3.7 NP NP 2 1.5 - 2.7 SP 0.9 NP NP 5 6.0 - 7.5 SP 0.9 NP NP 7 9.0 - 10.5 SP 0.9 NP NP 7 9.0 - 10.5 SP 0.0 NP NP 8 0.0 - 10.5 SP 0.0 NP NP	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%)	Sample Depth Unified Soil Moisture Percent No. Liquid Limit Flasticity Index (%) Percent (%) Fines (%) (%) <th< td=""><td>Sample Depth Unified Soil Moisture Percent No. Liquid Limit Flastic Limit Plastic Plasti</td><td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) <td< td=""><td>Sample Depth Unified Soil Moisture Percent No. Liquid Limit Plastic Limit Plasticity Index (%) Percent (%) Fines (%) (%)<td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP 7 9.0 - 10.5 SP 31.0 3.2 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 2.5 NP NP NP 4 4.5 - 5.5 SP 4.1 NP NP NP 1 0.0 - 1.0 SP 4.6 NP NP NP 5 6.0 - 6.9 SP</td></td></td<><td>Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plast</td><td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plastic Limit Plastic Limit Plastic Limit</td><td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastict Limit Plasticty Index (%) No. (Feet) Classification Symbol Content (%) (%)<!--</td--></td></td></th<>	Sample Depth Unified Soil Moisture Percent No. Liquid Limit Flastic Limit Plastic Plasti	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) <td< td=""><td>Sample Depth Unified Soil Moisture Percent No. Liquid Limit Plastic Limit Plasticity Index (%) Percent (%) Fines (%) (%)<td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP 7 9.0 - 10.5 SP 31.0 3.2 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 2.5 NP NP NP 4 4.5 - 5.5 SP 4.1 NP NP NP 1 0.0 - 1.0 SP 4.6 NP NP NP 5 6.0 - 6.9 SP</td></td></td<> <td>Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plast</td> <td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plastic Limit Plastic Limit Plastic Limit</td> <td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastict Limit Plasticty Index (%) No. (Feet) Classification Symbol Content (%) (%)<!--</td--></td>	Sample Depth Unified Soil Moisture Percent No. Liquid Limit Plastic Limit Plasticity Index (%) Percent (%) Fines (%) (%) <td>Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP 7 9.0 - 10.5 SP 31.0 3.2 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 2.5 NP NP NP 4 4.5 - 5.5 SP 4.1 NP NP NP 1 0.0 - 1.0 SP 4.6 NP NP NP 5 6.0 - 6.9 SP</td>	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plasticity Index (%) No. (Feet) Classification Symbol Content (%) Fines (%) (%) (%) (%) 5 6.0 - 7.2 GP 225.5 1.7 NP NP 6 9.0 - 10.0 32.3 NP NP NP 7 9.0 - 10.5 SP 24.8 2.0 NP NP 7 9.0 - 10.5 SP 31.0 3.2 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 0.4 2.5 NP NP 7 9.0 - 10.5 SP 2.5 NP NP NP 4 4.5 - 5.5 SP 4.1 NP NP NP 1 0.0 - 1.0 SP 4.6 NP NP NP 5 6.0 - 6.9 SP	Sample Depth Unified Soil Moisture Percent Liquid Limit Plastic Limit Plast	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastic Limit Plastic Limit Plastic Limit Plastic Limit	Sample Depth Unified Soil Moisture Percent Liquid Limit Liquid Limit Plastict Limit Plasticty Index (%) No. (Feet) Classification Symbol Content (%) (%) </td



l	% COBB	LES	% G	RAVEL	'	% SAN	1D	% SILT	%	CLAY	USCS	AASHTO	PL	
0			(52.6		35.7			1.7		GP	A-1-a		
-														
ſ	SIEVE		PER	CENT FI	NER		SIEVE	PE	RCENT FIN	NER		CRIPTION		
	inches size	0		, , , , , , , , , , , , , , , , , , , ,			number size	0				L, fine to coarse grav ts, some fine to mediu		sand
Ιſ	1	100.0	0				#4	37.4			tan	, IIIO 10 IIIO	4am 12	ourse,

size						
1 3/4 1/2 3/8	100.0 100.0 100.0 100.0					
> <	(GRAIN SIZE				
D ₆₀	6.49					
D ₃₀	1.11					
D ₁₀	0.356					
	COEFFICIENTS					
С _С	0.53					
C _c	18.21					

SIEVE	PE	RCENT FIN	IER
number size	0		
#4 #10 #20 #40 #60 #100 #200	37.4 33.0 26.6 12.6 6.6 3.7 1.7		
			

 GRAVEL, fine to coarse gravel sized fragments, some fine to medium quartz sand,
tan

REMARKS:

O Source: CB-JI00-1

Sample No.: 2

Elev./Depth: 1.5'-2.5'


Law Engineering and

Environmental Services, Inc.

Client: US Army Corp of Engineers

Project: Johns Island at West Palm Beach

Project No.: 50160-8-0025-JO11



	% COBBLES	% GRAVEL	% SAND	% SILT	% CLAY	USCS	AASHTO	PL	LL
0		0.5	97.5	2	.0	SP	A-3		
Γ									
_								T	

SIEVE	PE	RCENT FIN	ER
inches size	0		
.375	100.0		
		:	
	C	GRAIN SIZE	
D ₆₀	0.296		
D ₃₀	0.204		
D ₁₀	0.135		
$\supset \subset$	CC	DEFFICIEN	TS
C _c	1.04		
C _c	2.19		

SIEVE	PE	RCENT FIN	ER
number size	0		
#4 #10 #20 #40 #60 #100 #200	99.5 98.2 96.1 84.4 46.1 11.4 2.0		
0 1 3	T E		-

SOIL DESCRIPTION	14			
O SAND, fine quartz,	trace	sand	sized	shell
fragments, brown				

REMARKS:

0

O Source: CB-Л00-2

Sample No.: 5

Elev./Depth: 6.0'-7.5'


Law Engineering and Environmental Services, Inc.

Client: US Army Corp of Engineers

Project:

Johns Island at West Palm Beach

Project No.: 50160-8-0025-JO11



SIEVE	PERCENT FINER		
inches size	0		
.375	100.0		
> <	GRAIN SIZE		
D ₆₀	0.557		
D ₃₀	0.368	·	
D ₁₀	0.238		
$\supset <$	COEFFICIENTS		
C _c C _u	1.02		
Cu	2.34		

SIEVE	PERCENT FINER		
number size	0		
#4 #10 #20 #40 #60 #100 #200	100.0 99.8 94.2 39.7 11.3 5.9 3.7		
~			

SOIL DESCRIPTION
O SAND, fine quartz, trace sand sized shell
fragments, brown

REMARKS:

O Source:	CB-JI00-2	
O Douice.	CD-3100-2	

Sample No.: 7

Elev./Depth: 9.0'-10.5'

Law Engineering and

Environmental Services, Inc.

Client: US Army Corp of Engineers

Project: Johns Island at West Palm Beach

Project No.: 50160-8-0025-JO11